PATIO BLASTERS 800 SERIES [8 OHMS]



- 5 1/4" Polypropylene Coated Woofer
- Z way
- 1" Soft Dome Tweeter
- 5 Year Warranty
- 100 Watts Max
- Unique Trapezoidal Design
- · Ceiling or Wall Mount
- Aluminum Die-Cast Casing
- Tri-angle Bracket Included (30*, 45*, 90* options)
- Available in Black or White
- Available in 70 Volts







FEATURES

MODEL NUMBER:	T800	1870
DESCRIPTION:	5 114" 2-way	5 'Ar 2-way
OUTDOOR RATED:	YES	YES
IMPEDANCE:	8 Ohms	70 Volts
MAX POWER:	50 Watts	N/A
NOMINAL POWER:	100 Watts	N/A
TRANSFORMER TAP:	N/A	2.5, 5, 10, 15 Watts
SENSITIVITY (1W/1M)	89 dB	87 dB
FREQUENCY RESPONSE:	100 Hz - 22Hz	80 Hz - 22 Hz
CROSSOVER:	3.5 kHz	6 kHz
DISPERSION:	901	90°
WOOFER SIZE:	5 1/6ar	5 VP
WOOFER MATERIAL:	Polypropylane Coated	Polypropylene Coated
	Butyl Rubber Surround	Butyl Rubber Surround
TWEETER(S):	1	1
TWEETER SIZE:	1"	1,
TWEETER MATERIAL:	Soft Dome, WaveGuide	Soft Dome, WaveGuide
ENCLOSURE:	Aluminum Diecast	Aluminum Diecast
GRILL MATERIAL:	Aluminum	Aluminum
DIMENSIONS (LXWXH)	6 "" X 6" X 10"	6 ran X 6" X 10"
WEIGHT:	0.5 lbs.	890 lbs.
TRI-ANGLE BRACKET:	Included	Included
COLORS:	Black, White	Black, White

1874 5 1/1º 2-way YES 70 Volts N/A N/A 5, 10, 20, 40 Watts 89 dB 100 Hz - 22 Hz 6 kHz 90% 5 1/10 Polypropylene Coated Buryl Rubber Surround Soft Dome, WaveGulde Aluminum Diecast Aluminum 6 W X 6° X 10° 12.50 lbs

Included

Black, White

RECOMMENDED ACCESSORIE/S

S\$36 - In-Ground Stainless Stake (36°)

25WPVC - Water Proof Volume Control 25 Watt, Impedance Matching, 25W RM5

72WPVC - Water Proof Volume Control 25 Watt, Impedance Matching, 72W RMS

OWI 1070M - Attenuator, Mono, 70V, 10W Max

OWI3570M - Attenuator, Mono, 70V, 35W Max

OWI7570M - Attenuator, Mono, 70V, 75W Max

OW125705 - Attenuator, Stereo, 70V, 75W Max.



OWI incorporated

17141 Kingsview Avenue Cervan, CA 90746 USA ph. 510.515.1900 | 800.638.1694 fs. 310.515.1606 | e. Infeliowi-incomwww.ow-linc.com